A090 Line

	Backing	"A" weight paper.
	Mineral	Silicon Carbide.
	Grades	ANSI: 080 to 360.
CANDEL!	Coating	Open.
	Ideal	LACQUERS
		AND PAINT
114000	Recomme	ended
The second		WOOD AUTOMOTIVE PLASTIC NONFERROUS
	Shapes	ROLLOS SHEETS CONTACT SPECIALTIES
	Applicatio	ons
		n E P
GRADE AVAILABILITY		MANUAL SANDING ORBITAL ORBITAL SANDER PNEUMATIC WITH DISC SANDER SUCTION
080 100 120 150 180 220 240 280 320 360 MEDIUM / FINE / EXTRA FINE HEAVY POLISHING / INTERMEDIATE FINISHING / FINAL FINISHING		HOOK PSA ADHESIVE WET SANDING STEARATE DOESN'T CLOG
		LUBRICANT

Applications

- For sanding processes that require quick and aggressive action.
- For sanding plastics, fiberglass, polyester, nonferrous metals, plaster and drywall, ceilings, paints and other coatings like wall paste plasters, plasterboard joints and plaster ornaments, or smoothing wall inlay.

Characteristics

- Silicon Carbide guarantees a fast and powerful sanding action, producing high-quality finishes.
- > Their range of fine and medium grades makes them useful for various operations and finishes.
- > Silicon Carbide provides unique finishing characteristics.
- > The zinc stearate lubricating coat prevents premature clogging, ensuring a long shelf life of the product.



www.fandeli.com.mx 🛬