E088 Line

Ideal for use in the woodworking and metalworking industries.



Applications

ROLLS

Backing

Mineral

Grades

Coating

Ideal

Shapes



SHEETS

"E" weight paper.

Open.

W/OOD

Premium Aluminum Oxide.

FEPA: P036 to P320, except 280.


METAL

CONTACT



PSA ADHESIVE





PORTABLE

TANNERY

LACQUERS







SPECIALTIES

ESTAL PORTABLE B ERTICAL SANDER

GRADE AVAILABILITY

P036 P040 P050 P060 P080 P100 P120 P150 P180 P220 P240 P320

COARSE / MEDIUM / FINE / EXTRA FINE HEAVY GRINDING / INTERMEDIATE GRINDING / FINISHING

Applications

- For intermediate sanding and machine finishing of bare and treated wood.
- For high-quality finishes on hard woods, such as oak, which is a hard surface of fine porosity, lacquers, paints and nonferrous metals.
- Recommended product for working on quality furniture, such as floors or parquets, decorative locks and tabletops.
- Basic carpentry: baseboards, moldings, doors, windows, fences, wooden beams, and even shipbuilding and construction.
- For finishing operations that require low or intermediate pressures in the tannery industry.

Characteristics

GRIPIT

- Optimal performance under light and intermediate operating pressures.
- > Aggressive sanding action.
- Open structure prevents clogging and ensures a long shelf life.

